

A4 316 Equivalent Corrosion Resistance

S-BT-MR M8/15 SN 6
S-BT-MR M10/15 SN 6
S-BT-MR W10/15 SN 6

Hex nut with flange M8-A4
Hex nut with flange M10-A4
Hex nut with flange W10-A4

	SBT 4-A22
	TS-BT 5.5-74 S
	SBT 4-A22 SFC 18/22-A
	S-DG BT M8 / 15 Long 6
	S-DG BT M10 - W10 / 15 Long 6
	S-CC BT 6

Torque tool X-BT 1/4" 8 Nm / 5.9 ft.lb

S-NS 13 C 95/3 3/4" (M8)
S-NS 15 C 95/3 3/4" (M10)
S-NS 9/16" C 95/3 3/4" (W10)

1 GEAR #2 SBT 4-A22

2

3

4

5 SBT 4A-22 SFC 18/22-A GEAR #1

6

7 HILTI S-CC BT 6

9a Max. Max.

9b Min. Min.

10

11

8a HILTI S-CC BT 6

12a

8b HILTI S-CC BT 6

12b SBT 4-A22 SFC 18/22-A

12c $T_{inst} \leq 8 \text{ Nm}$

8c HILTI S-CC BT 6

S-DG BT M6 - W6 / 15 Long 6
S-DG BT M8 / 15 Long 6
S-DG BT M10 - W10 / 15 Long 6

CE
20
Hilti AG FL-9494 Schaan
Hilti-SF-DoP-029
ETA-20/0530
EAD 333037-00-0602
0672-CPR
Threaded studs for connection of materials to structural steel and aluminum members